


<b>Full-Quality Enterprise CO., LTD.</b>		<b>NO.</b>	2010002	<b>Book</b>	1
		<b>TotalPage</b>	1	<b>Page</b>	1
<b>Product Name</b>	<b>PE Form Double-Side High Performance Tape</b>				

Item NO. : FQ-208B

(DIMENSION):



Release Liner(White Paper)D/S SIDE  
Adhesion(Arcylic)

(MATERIAL PROPERTIES):

<u>TEST ITEM</u>	<u>VALUE</u>	<u>TEST METHOD</u>
1.Thickness (mm)	0.8+/-0.05	ASTM D-1000
2.Base Material(mm)	PE Form	
3.Thermal Conductive (K/W.K)	None	
4.180°Peel Adhesion (g/25 mm*25mm).	Over 1800	PSTC-1
5.Holding Power (1kg/inch)	Over 48hours	PSTC-7
6.Heat Resistance(0.5kg/inch) 120℃	Over 24hours	ASTM D-3330

(REMARK):

Expected Exterior Life: One Year  
Resistance Temperature Range: -20℃ to 120℃

(DIE-CUT STRUCTURE):

Half-cut in a piece

Issue Date	2009 年 05 月 1 日	Department	Issue	Review	Write
	2010 年 04 月 25 日	Quality Department		Sam	Peter