

Full-Quality Enterprise CO., LTD.		NO.	2009007	Book	2
		TotalPage	1	Page	1
Product Name	EMI Conductive High Performance Tape				

Item NO. : FQ-2100

(DIMENSION):



Alu. Foil(Alu. 0.05mm)
Adhesive+Nickel(Acrylic 0.03mm)
Release Liner(White Paper)S/S SIDE

(MATERIAL PROPERTIES):

<u>TEST ITEM</u>	<u>VALUE</u>	<u>TEST METHOD</u>
1.Total Thickness (mm)	0.08+/-0.05	ASTM D-1000
2.Base Material(mm)	Alu. Foil(0.05)	
3. Adhesive Thickness (mm)	0.03+Nickel	
4.180°Peel Adhesion (g/25 mm*25mm).	Over 1600	PSTC-1
5.Holding Power (1kg/inch)	Over 48hours	PSTC-7
6.Heat Resistance 120℃	Over 24hours	ASTM D-3330

(REMARK):

Expected Exterior Life: One Years
Resistance Temperature Range: -20℃ to 120℃

(DIE-CUT STRUCTURE):

HAFE-CUTTING IN A LOG ROLL

Issue Date	2008 年 07 月 1 日	Department	Issue	Review	Write
		Quality			
Update	2010 年 01 月 7 日	Department		Sam	Peter